

ZAL100 Series









- EFFICIENT RESULTS
 20x / 24x / 32x magnification
 360° graduation
 Up to 2 mm accuracy

CONSTRUCTION BUILT TOOLS Solid-built design IP54 protection Simple operation

COVERING EVERY NEED

- Full range of accessoriesShield Total Care





geomax-positioning.com ©2018 Hexagon AB and/or its subsidiaries and affiliates. All rights reserved.

ZAL100 Series

The GeoMax ZAL100 automatic levels are dependable, durable and economic tools designed for your daily levelling tasks on the construction site.

With three different types of magnification, a new solid-built design and IP54 protection as well as a full range of accessories and services, the GeoMax automatic levels provide great quality at affordable value.





EXPERTISE AT YOUR SERVICE

We care for your work and want your GeoMax tools to stay operational for as long as you work*.

Our highly skilled service centres support you around the world for the lifetime of your product.

COVER-ALL WARRANTY

The new GeoMax ZAL100 Series comes with a cover-all warranty for one year, protecting the tool from all defects that could occur during regular use, keeping you fully operational at all times and limiting downtime to the minimum.

Free of charge services during the warranty period:

- Repair (parts and labour) or exchange of your level
- Full functional and safety check

	ZAL120	ZAL124	ZAL132	
Accuracy telescope	2.5 mm	2.0 mm	2.0 mm	
Image	Erect	Erect	Erect	
Magnification	20 x	24 x	32 x	
Field of view	<2.1 m at 100 m	<2.1 m at 100 m	<2.1 m at 100 m	
Shortest target distance from instrument axis	< 1.0 m	< 1.0 m	< 1.0 m	

Protection

COMPENSATOR		
Working range	± 15′	
Setting accuracy**	0.5"	
ADAPTATION		
Central fixing screw***	5/8"	
DISTANCE MEASUREMEN	Т	
Multiplication factor	100	
Additive constant	0	

* The warranty	does not	cover	damage	caused	by	abuse	or m	ishandling

^{**} Standard deviation for 1 km double levelling ISO17123-2
*** To normal or ball head tripod





0818 - 768505 en

Copyright GeoMax AG.

Illustrations, descriptions and technical specifications are not binding and may change. All trademarks and trade names are those of their respective owners.

CIRCULAR LEVEL					
Sensitivity	8′/2 mm				
CIRCLE					
Graduation	360°				
Graduation interval	1°				
ENVIRONMENTAL					
Operating temperature	-20°C to +40°C (-4°F to +102°F)				



IP54



geomax-positioning.com

GEOMAX AUTHORISED DISTRIBUTION PARTNER